



रिब्दीकोट गाउँपालिका  
गाउँकार्यपालिकाको कार्यालय

खस्यौली, पाल्पा  
लुम्बिनी प्रदेश



०७५६२००५५, ०७५६९२३०७

Email: info@ribdikotmun.gov.np  
website: www.ribdikotmun.gov.np


प.सं.:- ०७८/७९  
च.न. १५२१०

मिति :- २०७९/०९/११

श्री विद्युतीय कारोबार गर्ने यस गाउँपालिकामा सूचिकृत सबै फर्महरु ।

विषय: दररेट पेश गर्ने सम्बन्धमा ।


प्रस्तुत विषयमा रिब्दीकोट गाउँपालिकाको कार्यालयको लागि निर्वाचन आयोगले तोकेको सिस्टिभि क्यामेरा र अन्य उपकरणहरु सहितको मतगणना स्थल दृश्य अवलोकन प्रणाली ( **Vote Counting Video Management System-VCVMS**) जडान गर्नु परेकोले पत्रको मितिले ७ दिन भित्र सोको दररेट यस कार्यालयमा उपलब्ध गराउनुहुन अनुरोध छ ।

  
.....  
(पबन अर्याल)  
प्रमुख प्रशासकीय अधिकृत  
प्रमुख प्रशासकीय अधिकृत

**Ribdikot Rural Municipality,  
office of the Municipal Executive, Khasauli Palpa**

*Technical Specification of vote counting video management system*

S.No.	CRITERIA	QTY	BUYER'S REQUIREMENT	OFFERED SPECIFICATION
1	2MP Lite Full-color Fixed-focal Bullet Network Camera	2	1.28" 2Megapixel fullcolor Max. Resolution 1920*1080(1fps-25-30fps),128MB RAM/ROM, ESS 1/3 s-1/100,000s,0.0017 Lux@F1.0.1080p (1920*1080);1.3 m(1280*960); 720p(1280*720); d1(704*576/704*480);VGA(640*480); CIF(352*288/352*240), Up to 40m,3.6mm:F1.06 mm: F1.0, Smart H. 2.65+/Smart H.264+, CBR/VBR,HLC.BLC,120 db WDR,3DNR,RJ-45(10/100Base-T), 2(Warm Light), Tripwire, Intrusion, 1 channel. Audio Input/Output, SDK/API, Motion Detection, 12VDC/PoE(802.3af), or equivalent	
2	2MP Lite Full-color Fixed-focal Eyeball Network Camera	6	1.28" 2Megapixel fullcolor Max. Resolution 1920*1080.128MB RAM/ROM, ESS Automannual 1/3 s-1/100,000s,0.0017 Lux@F1.0.1080p (1920*1080);1.3 m(1280*960); 720p(1280*720); d1(704*576/704*480);VGA(640*480); CIF(352*288/352*240), Up to 30 m.2(Warm Light). Pan; 0°/360°Tilt;0°-708° Rotation; 0°-360°;2.8 mm; F1.0 3.6 mm; F1.0, Tripwire, Intrusion,Motiondetection.Smart H.265+/Smart H.265+, RJ-45(10/100Base-T). CBR/VBR,HLC.BLC,120 db WDR, SDK/API,3DNR,Built-on-mic,12VDC/PoE(802.3af), or equivalent.	
3	8 channel NVR	1	NVR system: System and installation testing commissioning of NVR having 32 channel record. Smart H.265+; smart H.265+; H.264 : MJPEG 320Mbps incoming bandwidth, 2 SAT III ports up to 10 TB for a single HDD, Resolution:12 MP,8 MP, 6MP, 5MP, 4MP,3MP, 1080p, 1.3MP,720p, DI and more Alarm inputs/outputs:4/2, 1-RS-485, 1-HDMI,1-VGA, 1 RJ-45 10/100/1000 Mbps, 1 front USB 3.0 port, Perimeter protection: face detection and recognition :SMD plus: video metadata: AVPR : people counting stereo analysis :crowd distribution heat map,16-channel@1080 (30 fps) decoding 12V/4A DC or equivalent.	
4	10 Port Fast Ethernet Switch With 8-Port PoE	1	8- Port 100 Mbps +2-port Gigabit Managed PoE Switch > Intelligent PoE> Red Port support 90W IEEE802.3bt> Web Management with friendly interface and easy operation>250m Long distance PoE transmission > PoE Watchdog > Plug and Play or equivalent.	
5	19" surveillance Monitor	1	18.5" monitor > Industrial level LCD Panel suitable for continuous 24/7 operation > Light and cost effective plastic housing > High fidelity digital image blurring or ghosting > Low energy consumption, Low energy consumption, Long service life or equipment.	
6	2 TB-Surveillance Hard Drive	1	2TB/5400RPM/256/SATA6Gbs/s/DahuaSkyHawk, or equivalent	
7	CAT6 Network	2	UTP CAT6 Cable > 305.0m(1000 ft)/Carton UTP CAT6, power over Ethernet , Compatible with one cable >manufacturing excellence > customized PVC outer sheath meet CE CPR Eca frame retardant class certified > 10-years warranty or equivalent	
		1	DSS Professional V8 video surveillance base package includes 16 video channels and is a prerequisite for video channel expansion.Supported Live view, playback video wall, map event center deepxplore , maintenance center etc or equivalent	
		1	Video channel expansion license one video channel license for DSS professional V8 Prerequisite: Video surveillance base package or equivalent	

  
**Ribdikot Rural Municipality**  
 Office of the Rural Municipal Executive  
 Ribdikot, Palpa  
 Lumbini province, Nepal  
 2073

*Handwritten signature*